

# PRODUCT DATA SHEET

## ATLAS FR-10 / FR-50 FIRE BARRIER SLIPSHEETS

### Description:

Fire retardant coated mat (roof system component)

### Features

- Proprietary coating
- Flame retardant mat
- Tough and flexible
- Product Composition
- Lines marked on roll
- Convenient roll size

### Benefits

- Stabilized glass fibers
- Effective thermal barrier
- Handles wind and foot traffic
- Does not contribute to corrosion or mildew
- Easy alignment for overlapping
- Easy to handle on the roof



### Intended Use:

Thermal and fire barrier sheet listed by Underwriters Laboratories for use under Duro-Last roofing systems. FR 10/50 must be kept dry to retain its properties.

### Installation:

FR-10/50 is part of a UL fire listed assembly when installed to meet Duro-Last roofing specifications. The slipsheet should be rolled out and overlap the preceding sheets a minimum of 2-inches. On sloped applications or in windy conditions, use adequate fasteners and distribution plates to hold in place until the roofing membrane is installed.

FR-10 GENERAL INFORMATION	
Roll Size (4'x250')	1,000 sq.ft.
Coverage with 2" overlap	958 sq.ft.
Weight	.08 lbs./sq.ft.
	8 lbs./square
	80 lbs./roll

FR-50 GENERAL INFORMATION	
Roll Size (4'x105')	420 sq.ft.
Coverage with 2" overlap	402 sq.ft.
Weight	.18 lbs./sq.ft.
	18 lbs./square
	79 lbs./roll

For more information on these and other Duro-Last Products, contact the Duro-Last Engineering Services Department.

E-Mail: [engineering@duro-last.com](mailto:engineering@duro-last.com)

"Duro-Last" and the interlocking "DL" are registered marks owned by Duro-Last Roofing, Inc. October 2005



Duro-Last Roofing, Inc.  
525 Morley Drive  
Saginaw, MI 48601  
Ph: 1-800-248-0280  
Fax: 1-800-432-9331  
[www.duro-last.com](http://www.duro-last.com)