

# PRODUCT DATA SHEET

## ELK VERSASHIELD® FB-1S & FB-2S SLIPSHEET

### Description:

Patented fire barrier slipsheets (roof system component)

### Installation:

ELK VersaShield® The slipsheet should be rolled out and overlap the preceding sheets a minimum of 2-inches. On sloped applications or in windy conditions, use adequate fasteners and distribution plates to hold in place until the roofing membrane is installed.

### Storage/Shipping:

Keep dry in transport. Pallets must be stored on a flat surface and away from direct exposure to the elements. Do not store more than two pallets high.



### FB-1S GENERAL INFORMATION

Packaged:	Roll
Linear Feet/Roll	200 ft. minimum
Roll Width	42 in., ± 0.7%
Area per Roll	700 sq. ft. minimum
Roll Weight	70 lb. minimum
Fabric Weight	11.4 lb./100 sq.ft. min.

### FB-2S GENERAL INFORMATION

Packaged:	Roll
Linear Feet/Roll	100 ft. minimum
Roll Width	42 in., ± 0.7%
Area per Roll	350 sq. ft. minimum
Roll Weight	52.5 lb. minimum
Fabric Weight	18.1 lb./100 sq.ft. min.

For more information on these and other Duro-Last Products, contact the Duro-Last Engineering Services Department.

E-Mail: [engineering@duro-last.com](mailto:engineering@duro-last.com)

"Duro-Last" and the interlocking "DL" are registered marks owned by Duro-Last Roofing, Inc. October 2005



Duro-Last Roofing, Inc.  
525 Morley Drive  
Saginaw, MI 48601  
Ph: 1-800-248-0280  
Fax: 1-800-432-9331  
[www.duro-last.com](http://www.duro-last.com)