

PRODUCT DATA SHEET

EYEHOOK™ METAL PLATE

Description:

The EyeHook™ Metal Plate is .035" thick, 2-3/8" inch diameter galvalume plate. The Galvalume finish has proven weatherability and resiliency. The EyeHook™ Metal Plates are packaged and sold in quantities of 1000.

EyeHook™ Metal Plates are stamped to include a recessed 0.265-inch (6.7 mm) diameter hole in the center and a series of ribs for added strength. The configuration of the ribs and the hole is used to prevent the screw head from coming in contact with the Duro-Last® Roofing membrane.

In addition to the stamped ribs, there are "eye hooks" stamped into the plate to hold the Duro-Last® Roofing membrane in place without tearing or puncturing the membrane in high-stress load applications. Also, because the barbs are not sharp, they are easier to handle.

The EyeHook™ Metal Plate is a long-lasting and durable plate that is available from Duro-Last® Roofing, Inc.

Installation:

The EyeHook™ Metal Plate must be used for securing the Duro-Last® membrane to the deck along the prefabricated fastening tabs and the edges of the sheet parallel to the tab direction. The EyeHook™ Metal Plate must be installed with the edge flush to the edge of the fastening tab. If used with the Duro-Roof® System, the plate must be installed on the center of the 6" fastening tab.

The EyeHook™ Metal Plate is limited to the installation of Duro-Last® Roofing membrane directly over hard substrates (wood, OSB, gypsum board, Dens Deck, lightweight and structural concrete, etc.).

For more information on these and other Duro-Last Products, contact the Duro-Last Engineering Services Department.

E-Mail: engineering@duro-last.com

