

PRODUCT DATA SHEET

DURO-LAST GRAVEL STOP

Description:

Duro-Last® Patented Gravel Stop (available in white, gray, and tan) is fabricated from a rigid exterior vinyl with a 6" skirt (also available in white, gray, and tan) made from a high tenacity low-shrink weft-inserted 18 x 14, 1,000 Denier polyester fabric that has been coated with a proven thermoplastic alloy. Duro-Last® patented Gravel Stop may be used as perimeter for the Duro-Last® Roofing System.

Duro-Last® Gravel Stop is available in two face sizes: 2½" (51 mm) and 4" (102 mm). The Gravel Stop is available in 10' (3 m) lengths. Duro-Last® has pre-punched slotted holes 8" (203 mm) on center for fastening of the Gravel Stop. Duro-Last® provides joint clips for the face to improve and enhance aesthetics. Special orders can be produced to alter the skirt size and color to provide for the desired aesthetics (Example: white material on tan Gravel Stop or tan material on white Gravel Stop).

Duro-Last® Gravel Stop Edge has been successfully tested by Factory Mutual Research Corporation as an approved edging component for FM 1-90 roof assemblies.

Duro-Last® Gravel Stop is packed in either small tubes or large boxes in multiples of 10' (3 m). A small tube will contain 50 linear feet (15.2 m) of 2½" (51 mm) face Gravel Stop, while a large box will contain 200 linear feet (61 m) of 2½" (51 mm) face Gravel Stop. The 4" (102 mm) face Gravel Stop can be packaged in a large box holding a maximum of 140 linear feet.

Installation:

Duro-Last® Gravel Stop skirting shall be heat-welded (hot-air) to the field membrane. The Gravel Stop with attached skirt shall be fastened to deck/wood nailers only with approved fasteners, spaced 8 inches (.2 m) on center. Gravel stop can be installed on any flat edge including the top of parapet walls. It is necessary to allow 1 inch (25 mm) spacing at all joints; the joint clips will cover this space. Pre-manufactured outside Duro-Last® Gravel Stop corners may be used for aesthetic value.

For more information on these and other Duro-Last Products, contact the Duro-Last Engineering Services Department.

E-Mail: engineering@duro-last.com

