

# PRODUCT DATA SHEET

## DURO-LAST POLYETHYLENE SLIPSHEET

### Description:

Duro-Last® polyethylene construction sheeting is a low-cost separation sheet used in conjunction with the Duro-Last® Roofing System. The polyethylene is chemical-resistant and has excellent weatherability characteristics. The sheeting is 3-mil (minimum) thick and is available in 20' x 100' rolls. The polyethylene is a clear film made of inert organic materials, does not provide nutritive value to plants, animals, or microorganisms, and is highly resistant to mildew.



### Basic Use:

Duro-Last® polyethylene has been designed to protect PVC membranes from residual materials on roof decks and parapet walls. This 3 mil film provides a barrier to PVC plasticizers, which might otherwise have chemical reactions with EPS and/or other incompatible material.

GENERAL INFORMATION	
Width x Length	20' x 100'
Color	Clear
Square Feet per Roll	2000
Roll Weight	28.7 Lbs

### Installation:

Duro-Last® polyethylene should be unfolded and placed over existing applicable roofs. Fasten the polyethylene with as many fasteners necessary to temporarily hold in place. Membrane can then be installed over this assembly with mechanical fasteners per Duro-Last® specifications.

For more information on these and other Duro-Last Products, contact the Duro-Last Engineering Services Department.

E-Mail: [engineering@duro-last.com](mailto:engineering@duro-last.com)

"Duro-Last" and the interlocking "DL" are registered marks owned by Duro-Last Roofing, Inc. October 2005



Duro-Last Roofing, Inc.  
525 Morley Drive  
Saginaw, MI 48601  
Ph: 1-800-248-0280  
Fax: 1-800-432-9331  
[www.duro-last.com](http://www.duro-last.com)