

# DURO-LAST® MEMBRANE 2-MINUTE FACT SHEET







#### The Duro-Last Difference:

The Duro-Last flagship membrane is a proprietary thermoplastic formulation that provides exceptional flexibility and reflectivity. Available in 40, 50, and 60 mil thickness, the Duro-Last membrane can be custom-fabricated to meet the exact specifications of the building. With the custom-fabricated Duro-Last Roofing System, up to 85% of seams can be completed in our factory-controlled environment, dramatically reducing rooftop labor and the potential for leaks. Additionally, the Duro-Last membrane features an 18 x 14 weft-insertion anti-wicking scrim, providing superior strength and puncture resistance.

## The Duro-Last Membrane can be applied using a variety of methods:

- Duro-Bond® Induction Welding:
   A non-penetrating technology that bonds the membrane to a specialty-coated fastening plate.
- Adhered:
   Duro-Last offers several adhesive options for applying the roof membrane to the deck surface.
- Mechanical Attachment:
   Fasteners and plates are used to securely attach sections of membrane to the roof deck.

#### **Precision-Fabricated Accessories:**

The Duro-Last Membrane also features its own complete line of compatible custom-fabricated flashings, skirted edge metal made by EXCEP-TIONAL® Metals, and other roofing system components. Custom-fabricated flashings are manufactured with Duro-Last membrane material and feature a weft-inserted scrim that provides puncture and tear resistance along with tensile strength at transitions – the most critical areas of any roof installation.

### **Comprehensive Warranty Coverage:**

Unique in the industry, Duro-Last offers a 15-Year Supreme Warranty with consequential damage coverage for commercial applications of the Duro-Last Roofing System. Additional Supreme warranties, as well as our Basic, Ultra, and Residential warranties are also available. Hail and high-wind warranties can also be obtained for Duro-Last installations.

#### **Color Swatches**



DURO-LAST MEMBRANE			
MIL	40	50	60
Weight	.22 lb/sq ft	.29 lb/sq ft	.36 lb/sq ft
Scrim	18 x 14	18 x 14	18 x 14
Custom Dimensions	Deck sheets up to 2,500 ft.2*	Deck sheets up to 2,000 ft.2**	Deck sheets up to 1,500 ft.2***
PVC Film Above Scrim	17 mil	28 mil	28 mil

<sup>\*</sup> Maximum length or width of 100 feet in either direction

<sup>\*\*</sup> Maximum length or width of 80 feet in either direction

<sup>\*\*\*</sup> Maximum length or width of 60 feet in either direction. 60-mil sections are delivered on carpet rolls only and may be ordered with a maximum sheet length of 24 feet, as the carpet roll is 25 feet long. When shipped, the rolls may be wrapped in a different colored membrane for membrane protection.