



DURO-LAST SOLVENT-GRIP® AND SOLVENT-GRIP® PLUS SPRAY ADHESIVE

Increase labor savings and rooftop efficiencies with the self-contained, low volatile organic compound (VOC) Duro-Last Solvent-Grip and Solvent-Grip Plus Spray Adhesive systems. Duro-Last Solvent-Grip is ideal for bonding Duro-Last®, Duro-Last X™ and Duro-Tuff® membranes to a variety of substrates on horizontal and vertical surfaces. Duro-Last Solvent-Grip Plus is ideal for bonding Duro-Last, Duro-Last X, Duro-Tuff and Duro-Last EV membranes to a variety of substrates on horizontal and vertical surfaces. Full bond strength achieved within 24 hours of application.

SOLVENT-GRIP PROPERTIES	
Consistency	Aerosol spray
Weight	40 lb. / cylinder
Spray Pattern	Variable web
Odor	Acetone smell
Base	Synthetic rubber and resin
Dry Time	3 to 5 minutes*
Service Temperature	-30 to 180 F (-34 to 82 C)
Flammability	Flammable when wet, non-flammable when dry
Shelf Life	12 months (unopened cylinder)
VOC Content	240 g / L (EPA method 24)
Prop 65	"WARNING! This product can expose you to chemicals which are known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov ."

* Depending upon climate conditions

SOLVENT-GRIP PLUS PROPERTIES	
Consistency	Aerosol spray
Weight	7.32 lb. / gallon (0.88 kg. / L)
Spray Pattern	Variable web
Odor	Solvent smell
Base	Synthetic polymer
Dry Time	3 to 10 minutes*
Service Temperature	-30 to 200 F (-34 to 93 C)
Flammability	Flammable when wet, non-flammable when dry
Shelf Life	12 months (unopened cylinder)
VOC Content	232.5 g / L (EPA method 24)
Prop 65	"WARNING! This product can expose you to chemicals which are known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov ."

* Depending upon climate conditions

